

TBX SERIES

PORTABLE ELECTRIC HEATER



IDEAL SPACES

- Building Construction
- Drywall Dry-Out
- Factories
- Stores
- Warehouses
- Greenhouses
- Stock Rooms
- Flood Dry-Out Areas
- Workshops
- Repair Stations
- Tent Heating
- Frozen Pipe Thaw-Out

COLORS

- Red

DIMENSIONS

- 28.5"H x 25"W x 18.5"D

- High BTU per hour heater without the exhaust fumes or moisture associated with gas heat
- Heats lower to the floor for natural convection
- Includes 8 ft. cord and NEMA 6-50P plug
- Convenient storage area under lid for tools and accessories
- Collapsible handle for easy transport and storage
- Thermostat with positive OFF (40°- 100°F)
- Fan-only mode for air recirculation, fume exhaust or fresh air supply
- Over temperature limit protects unit from low air flow conditions
- Lower profile to prevent tipping



TBX SERIES

PORTABLE ELECTRIC HEATER

MODELS & SPECIFICATIONS

CATALOG NO.	UPC	KW	VOLTS	AMPS	BTU/HR	CFM	DIMENSIONS (IN)	SHIP WT. (LBS.)
TBX104	6 85360 15127 4	9.5	240	39.6	32,424	1100	28.5" H x 25" W x 18.5" D	70
TBX754	6 85360 15128 1	7.5	240	31.2	52,598	1100		