

AWH SERIES

Architectural Heavy-Duty Wall Heater

WALL HEATERS



Bronze and White

Technical Specifications:

Temp Range: 40°-90°F

CFM: 100

Grille Gauge: 18

Ideal Spaces:

Vestibules & Entrance Ways

Lobbies & Hallways

Stairwells

Restaurants


Conference Rooms

Offices

Basements

Living/Family Room

- › BMS-compatible through an optional relay
- › Contemporary bar-stock grille design provides optimized airflow
- › Manual reset thermal overheat protector disconnects power in the event of accidental blockage
- › Built-in tamper-resistant thermostat
- › All units have a permanently lubricated and enclosed fan motor, which creates long life, low maintenance, and gently distributes warmth throughout the area
- › Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- › Power on/off switch for added safety during maintenance



White



Bronze



AWH SERIES

Architectural Heavy-Duty Wall Heater

Scan the QR code
to access additional
specs and features



Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA					SHIP WT.
CATALOG NO.	UPC	VOLTS	PHASE	WATTS	AMPS	BTU/HR.		
◆ AWH3150F	685360161860	120	1	1500	12.5	5,118	25 lbs	
◆ AWH4307F	685360161945	277	1	3000/1500	10.8/5.4	10,236/5,118	25 lbs	
◆ AWH4404F*	685360161983	240	1	4000/2000	16.7/8.3	13,649/6,824	25 lbs	
		208	1	3000/1500	14.4/7.2	10,236/5,118	25 lbs	
◆ AWH4407F*	685360162065	277	1	4000/2000	14.4/7.2	13,649/6,824	25 lbs	
		240	1	3000/1500	12.5/6.3	10,236/5,118	25 lbs	
◆ AWH4408F	685360162102	208	1	4000/2000	19.2/9.6	13,649/6,824	25 lbs	
◆ AWH4504F*	685360162188	240	1	4800	20	16,378	25 lbs	
		208	1	3600	17.3	12,284	25 lbs	
◆ AWH4507F*	685360162263	277	1	4800	17.3	16,378	25 lbs	
		240	1	3600	15	12,284	25 lbs	
◆ AWH4508F	685360162300	208	1	4800	23.1	16,378	25 lbs	
● AWH3180F	685360161884	120	1	1800	15	6,142	25 lbs	
● AWH44043F	685360162027	240	3	4000	9.6	13,649	25 lbs	
● AWH44083F	685360162140	208	3	4000	11.1	13,649	25 lbs	
● AWH45043F	685360162348	240	3	4800	11.6	16,378	25 lbs	
● AWH45083F	685360162225	208	3	4800	13.3	16,378	25 lbs	
● AWH4303F	685360164021	347	1	3000	8.6	10,236	25 lbs	
● AWH4503F	685360164106	347	1	4800	13.8	16,378	25 lbs	
● AWH4306F	685360164069	600	1	3000	5	10,236	25 lbs	
● AWH4506F	685360164144	600	1	4800	8	16,378	25 lbs	

SKU Legend: ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

NOTE: *Factory-wired for higher wattage, field-convertible to half wattage. Units not available to be wired with remote thermostats. Standard finish is Bronze; For White, add NW suffix to catalog number.

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
AWHPE*	685360007212	Pneumatic/Electric switch. Factory set at 10 psig to "make" on pressure drop. May be field wired to "break" on pressure drop. Pressure set point adjustable to 30 psig. (field-installed)	2 lbs
AWHR2 (24V)*	685360007236	Time delay relay 40-60 seconds to close when energized. Use 120V or 24V power supply from remote source (field-installed)	2 lbs
AWHR12 (120V)*	685360007229		
AWHS1	685360007267	1 in. deep surface mounting frame for semi-recessed installation, Bronze	2 lbs
AWHS2	685360007281	2 in. deep surface mounting frame for semi-recessed installation, Bronze	2 lbs
AWHSM	685360007243	Surface mounting frame for surface installations. Painted to match heater decor, 3 13/16 in. deep, Bronze	5 lbs
LFKSFCNW	685360160795	14-gauge security front cover, White	6 lbs

Note: *Will accommodate pneumatic/electric or low-voltage controls commonly used with computerized energy management systems Mounting Limitations: For wall mounting, do not install back box closer than 8 in. from floor or adjacent wall. Do not install heater behind towel rack, behind door, in floor, in closet, in ceiling or where air flow may be obstructed. All controls are concealed behind the front cover making them essentially tamper proof.

Dimensions and Clearances:

