

# CHPR25 SERIES

## Plenum-Rated Unit Heater

Concealed Space Use – Zero Clearance

# UNIT HEATERS



### Technical Specifications:


Temp Range: 40°-90°F

CFM: 150

### Ideal Spaces:

Between Finished  
Ceiling & Drop Ceiling

Plenum Areas  
Freeze Protection



Beige

- › Plenum-rated approved for installations in concealed spaces (between finished ceiling and drop ceiling, plenum space, or inside a plenum). It may be installed in areas that are not readily accessible and may be installed for freeze protection
- › 18-gauge all steel casing with polyester powder coat finish for corrosion protection
- › Steel finned low-watt density element. High limit thermal cutout automatically shuts off current in event of overheating and reactivates the heater when temperature returns to normal
- › Fan delay control. feature allows only warm air to be distributed; optional alarm (240V) to alert automatic thermal limit tripped (Model AFL240)
- › Built-in thermostat
- › Control box gasket to keep out moisture and dust; NEMA 12 construction
- › Fan motor completely enclosed, permanently lubricated and thermally protected
- › Single point field wiring connection for easy installation and maintenance



Intertek



# CHPR25 SERIES

## Plenum-Rated Unit Heater

Scan the QR code  
to access additional  
specs and features



### Models & Specifications:

ITEM INFORMATION		ELECTRICAL DATA								SHIP WT.
CATALOG NO.	UPC	VOLTS	kW	AMPS	PHASE	HZ	BTU/HR.	FPM	RISE	SHIP WT.
◆ CHPR25	685360149547	240	2.5	10.7	1	60	8530	1880	60° F	26 lbs
		208	1.9	9.42		60	6398		46° F	

SKU Legend: ◆ = Popular Products ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

### Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
AFL240	685360153476	Thermal Limit Alarm	1 lbs

### Dimensions and Clearances:

