

# FDI SERIES

## Floor Drop-In Heater

PORTABLE &  
SPECIALTY HEATERS



### *Technical Specifications:*

Temp Range: 55°-90°F  
CFM: 80

### *Ideal Spaces:*

Vestibules  
Hallways  
Bathrooms  
Bedrooms



Charcoal

For ground level comfort, choose a drop-in unit heater. These units are specifically designed to be placed into flooring for an unobtrusive heating solution that keeps building occupants warm without taking up extra space.

- › Universal size combined with a heavy-duty steel grille for durability
- › Quick Installation - mounts between floor joists parallel or perpendicular
- › Overheat thermal protection for peace of mind
- › Flow pattern is 5 ft. wide and 4 ft. high
- › Push-on tab wire terminals for easy and quick installation
- › Quiet operation



# FDI SERIES

## Floor Drop-In Heater

Scan the QR code  
to access additional  
specs and features



### Models & Specifications:

ITEM INFORMATION		ELECTRICAL DATA				SHIP WT.
CATALOG NO.	UPC	CFM	VOLTS	WATTS	AMPS	
◆ FDI1500	685360026268	80	120	1500/750	12.5/6.3	10 lbs
◆ FDI1504	685360026282	80	240	1500/750	6.3/3.1	10 lbs
		80	208	1125/562	5.4/2.7	

**SKU Legend:** ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

NOTE: 60 Hz single-phase. Do not install in bathroom or other areas where water may enter heater unit. Do not locate where air flow may be obstructed (under drapes, behind doors, etc.). Keep short side 36 in. min. and long side 3 in. min. from side walls. Do not install in ceiling or wall.

### Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
FDITSP	685360026190	120-240V Thermostat Kit	1

### Dimensions and Clearances:

