

HT RESIDENTIAL SMARTSERIES®

Programmable Wall Heater

WALL HEATERS




Technical Specifications:


Temp Range: 40°-99°F
CFM: 100

Ideal Spaces:

Kitchens
Bathrooms
Basements
Offices & Waiting Rooms
Conference Rooms
Hallways
Lobbies
Vestibules and Entrance Ways



White



Gray

- › Heater automatically adjusts wattage output and blower speed for whisper-quiet operation and optimum comfort
- › Heating element is heavy-duty, non-glowing steel fins brazed to steel sheathed tubular elements placed in grid pattern that covers the entire discharge area
- › Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- › SmartSeries® Digital Thermostat: 5/2-day programming with four periods per day
- › Contemporary, clean design with easy to use LED touch screen
- › Easy installation—heater is mounted prior to wiring. Both hands are free to make field connections in spacious compartment



HT RESIDENTIAL SMARTSERIES®

Programmable Wall Heater

Scan the QR code
to access additional
specs and features



Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA					SHIP WT.
CATALOG NO.	UPC	VOLTS	PHASES	WATTS	AMPS	BTU/HR.		
HT2024SS	685360153513	240	1	2500/2000	1.0/8.3	853/6826	20 lbs	
HT1502SS	685360153506	120	1	2000/1500	1.6/12.5	682/5120	20 lbs	
HT2024SSNW	685360158549	240	1	2500/2000	1.0/8.3	853/6826	27 lbs	
HT1502SSNW	685360158525	120	1	2000/1500	1.6/12.5	682/5120	27 lbs	

SKU Legend: = Popular Products; = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

Optional Accessories

CATALOG NO.	UPC	DESCRIPTION	DESCRIPTION	SHIP WT.
SMHTSSSNW	685360156316	White Surface Mounting Frame, 14 5/8" W x 20 1/4" H x 3 3/4" D	White	2.6 lbs
SMHTSSBL	685360156309	Black Surface Mounting Frame, 14 5/8" W x 20 1/4" H x 3 3/4" D	Black	2.6 lbs

NOTE: Mounting Limitations: Do not install heater closer than 12 in. to the floor, 12 in. to an adjacent wall, 36 in. to the ceiling. Do not install heater behind towel rack or door, upside down or sideways, in the floor, in the ceiling, or in closets.

Dimensions and Clearances:

