

DIRECT DRIVE MAN-COOLERS



Low Stand



Medium Stand



High Stand

- Rugged, heavy duty 18" to 48" cooling fans,
- Available with totally enclosed or explosion proof motors
- Non-sparking, cast aluminum props
- 14 Gauge steel body
- Enamel coating standard, optional acid resistant coating
- Manual starter switches available
- 360° Swivel on high and medium stand units
- Meets Federal OSHA requirements
- 1 Year Limited Warranty

FAN SIZE	ORDER NUMBER*		HP	RPM	0" SP CFM	DB @10'	WT.	LIST				
	115/230V 60HZ 1 PH.	230/460V 60HZ 3 PH.						TE		EXP		
								1 PH.	3PH.	1 PH.	3PH.	
HIGH STAND MODELS												
18	18H141	18H143	1/4	1725	3050	72	228	•	•	•	•	
	24H141	24H143	1/4	1725	5200	78	255	•	•	•	•	
24	24H121	24H123	1/2	1725	6000	78	260	•	•	•	•	
	24H341	24H343	3/4	1200	7000	72	280	•	•	•	•	
	24H11	24H13	1	1725	7400	80	270	•	•	•	•	
	24H31	24H33	3	1725	10500	85	300	•	•	—	•	
30	30H121	30H123	1/2	1725	8000	84	281	•	•	•	•	
	30H341	30H343	3/4	1200	9000	78	350	•	•	•	•	
	30H1121	30H1123	1 1/2	1725	11000	90	340	•	•	•	•	
	30H21	30H23	2	1200	12000	82	365	•	•	—	•	
36	30H31	30H33	3	1725	13000	92	360	•	•	—	•	
	36H1121	36H1123	1 1/2	1725	14850	86	420	•	•	•	•	
	36H21	36H23	2	1725	16000	86	420	•	•	•	•	
	36H2A1	36H2A3	2	1200	14000	80	420	•	•	—	•	
42	—	36H33	3	1150	19000	82	425	—	•	—	•	
	—	42H23	2	1150	19500	84	565	—	•	—	•	
48	—	42H53	5	1150	27000	84	590	—	•	—	•	
	—	48H7123	7 1/2	1150	33000	103	875	—	•	—	•	
MEDIUM STAND MODELS												
18	18M141	18M143	1/4	1725	3050	72	163	•	•	•	•	
	24M141	24M143	1/4	1725	5200	78	165	•	•	•	•	
24	24M121	24M123	1/2	1725	6000	78	180	•	•	•	•	
	24M341	24M343	3/4	1200	7000	72	200	•	•	•	•	
	24M11	24M13	1	1725	7400	80	190	•	•	•	•	
	24M31	24M33	3	1725	10500	85	220	•	•	—	•	
30	30M121	30M123	1/2	1725	8000	84	201	•	•	•	•	
	30M341	30M343	3/4	1200	9000	78	270	•	•	•	•	
	30M1121	30M1123	1 1/2	1725	11000	90	260	•	•	•	•	
	30M21	30M23	2	1200	12000	82	285	•	•	—	•	
36	30M31	30M33	3	1725	13000	92	280	•	•	—	•	
	36M1121	36M1123	1 1/2	1725	14850	86	320	•	•	•	•	
	36M21	36M23	2	1725	16000	86	325	•	•	•	•	
	36M2A1	36M2A3	2	1200	14000	80	325	•	•	—	•	
42	—	36M33	3	1150	19000	82	350	—	•	—	•	
	—	42M23	2	1150	19500	84	415	—	•	—	•	
48	—	42M53	5	1150	27000	84	440	—	•	—	•	
	—	48M7123	7 1/2	1150	33000	103	745	—	•	—	•	
LOW STAND MODELS												
18	18L141	18L143	1/4	1725	3050	72	103	•	•	•	•	
	24L141	24L143	1/4	1725	5200	78	115	•	•	•	•	
24	24L121	24L123	1/2	1725	6000	78	120	•	•	•	•	
	24L341	24L343	3/4	1200	7000	72	140	•	•	•	•	
	24L11	24L13	1	1725	7400	80	130	•	•	•	•	
	24L31	24L33	3	1725	10500	85	160	•	•	—	•	
30	30L121	30L123	1/2	1725	8000	84	141	•	•	•	•	
	30L341	30L343	3/4	1200	9000	78	210	•	•	•	•	
	30L1121	30L1123	1 1/2	1725	11000	90	200	•	•	•	•	
	30L21	30L23	2	1200	12000	82	225	•	•	•	•	
36	30L31	30L33	3	1725	13000	92	220	•	•	—	•	
	36L1121	36L1123	1 1/2	1725	14850	86	250	•	•	—	•	
	36L21	36L23	2	1725	16000	86	255	•	•	•	•	
	36L2A1	36L2A3	2	1200	14000	80	255	•	•	•	•	
42	—	36L33	3	1150	19000	82	260	•	•	—	•	
	—	42L23	2	1150	19500	84	315	—	•	—	•	
48	—	42L53	5	1150	27000	84	340	—	•	—	•	
	—	48L7123	7 1/2	1150	33000	103	625	—	•	—	•	

Optional Casters for Low & Medium Stand Man-coolers

- Factory installed
- 2 Fixed and 2 Swivel casters per model

* NOTE: When ordering Explosion Proof models, add EXP suffix to model number

Optional Accessories

ORDER NUMBER	FAN SIZE	WHEEL SIZE	SHIPPING WEIGHT
CAS18	18"- 30"	4"	10 lbs.
CAS48	36"- 48"	6"	14 lbs.

NOTE: When ordering explosion proof model add EXP. suffix to model number.