



## INDUSTRIAL FLOOR AIR CIRCULATOR



**IR18 Rollaire**



**I12 & I18**



<b>Motor</b>	3-speed, 1Ø, 115 volt sleeve bearing open drip proof permanently lubricated.
<b>Switch</b>	Rotary
<b>Cord</b>	10' long 3-conductor SJT Type
<b>Blade</b>	Painted steel
<b>Guard</b>	Double locking, chrome plated*
<b>Fan Head Tilt</b>	360°

Meets OSHA standards / 1 year limited warranty  
\* IR18 provided in black finish only.

### Ordering Summary

BLADE SIZE	ORDER NUMBER	CFM			HP	AMPS (HIGH)	SHIPPING WEIGHT
		HIGH	MED	LOW			
12"	<b>I12</b>	2650	2100	1550	1/15	1.2	8 lbs.
18"	<b>I18</b>	5500	4600	3400	1/8	2.6	16 lbs.
18"	<b>IR18#</b>	5500	4600	3400	1/8	2.6	24 lbs.
18"	<b>*I18TE</b>	5500	4600	3400	1/8	2.6	16 lbs.
20"	<b>I20</b>	5950	4650	3500	1/8	2.6	20 lbs.
24"	<b>I24</b>	6500	4800	3500	1/8	2.0	31 lbs.

\*I-18TE has a 115V 1Ø totally enclosed motor for dirty environments. 10' Long 3 conductor SJT Type cord. 360° fan head tilt meets OSHA/UL/cUL.  
1 year limited warranty. # Some assembly required.