



- 24" to 60" Sizes available with 115/230V 1 or 230/460V3, totally enclosed fan cooled, permanently lubricated motors
- 16 Gauge steel venturi with steel pipe bracing
- Steel blades
- Double pillow block bearing shaft support

Options:

- WS Shutters
- FG Front Guards
- RBG Rear Guards
- Industrial grey enamel finish
- Fans shipped completely assembled, factory tested and adjusted, ready to install
- 1 Year Limited Warranty
- Use Web Model for Explosion Proof or Intake Applications

Ordering Summary

BLADE DIA.	1-PHASE		3-PHASE		PANEL SIZE SQ."	HP	RPM	CFM 0" SP	APPROX. WEIGHT	LIST	
	115/230V MODEL NO.	208-230/460V MODEL NO.	HP	RPM						1 PH.	3 PH.
24"	PEF24131	PEF24133	30"	1/3	825	5300	70 lbs.	•	•		
	PEF24121	PEF24123		1/2	925	6200	72 lbs.	•	•		
	PEF24341	PEF24343		3/4	1050	7000	80 lbs.	•	•		
	PEF2411	PEF2413		1	1175	7800	90 lbs.	•	•		
30"	PEF30131	PEF30133	36"	1/3	570	7500	108 lbs.	•	•		
	PEF30121	PEF30133		1/2	625	8500	110 lbs.	•	•		
	PEF30341	PEF30343		3/4	725	10000	116 lbs.	•	•		
	PEF3011	PEF3013		1	825	11000	126 lbs.	•	•		
36"	PEF36131	PEF36133	42"	1/3	425	9000	131 lbs.	•	•		
	PEF36121	PEF36123		1/2	500	10500	133 lbs.	•	•		
	PEF36341	PEF36343		3/4	575	11900	138 lbs.	•	•		
	PEF3611	PEF3613		1	650	13100	145 lbs.	•	•		
	PEF361121	PEF361123		1 1/2	750	15000	155 lbs.	•	•		
	—	PEF3623		2	830	16500	170 lbs.	—	•		
42"	PEF42341	PEF42343	48"	3/4	430	14000	158 lbs.	•	•		
	PEF4211	PEF4213		1	490	15400	166 lbs.	•	•		
	PEF421121	PEF421123		1 1/2	550	17200	181 lbs.	•	•		
	—	PEF4223		2	620	19400	191 lbs.	—	•		
	—	PEF4233		3	700	22000	201 lbs.	—	•		
48"	PEF4811	PEF4813	54"	1	400	19100	174 lbs.	•	•		
	PEF481121	PEF481123		1 1/2	460	22000	178 lbs.	•	•		
	—	PEF4823		2	520	24000	194 lbs.	—	•		
	—	PEF4833		3	590	27500	204 lbs.	—	•		
	—	PEF4853		5	660	30500	234 lbs.	—	•		
60"	—	PEF6023	66"	2	320	31000	328 lbs.	—	•		
	—	PEF6033		3	370	35000	342 lbs.	—	•		
	—	PEF6053		5	420	39000	352 lbs.	—	•		