



- 18" to 36" Direct drive blowers available with one way or two way swivel
- Mount to overhead beams or wall columns
- Available with totally enclosed or explosion proof motors
- Non-sparking, cast aluminum blades
- 14 Gauge steel body, steel tubing yoke
- Front and rear spiral guards
- Meets Federal OSHA requirements
- 1 Year Limited Warranty

### 1 Way Swivel

BLADE DIA.	1-PHASE 115/230V ORDER NO.	3-PHASE 230/460V ORDER NO.	NO. OF BLADES	HP	RPM	0" SP CFM	DB @ 10'	WT.	LIST			
									TE		EXP	
									1 PH.	3 PH.	1 PH.	3 PH.
18	18S141	18S143	4	1/4	1725	3050	72	163	•	•	•	•
	24S141	24S143	2	1/4	1725	5200	78	165	•	•	•	•
24	24S121	24S123	4	1/2	1725	6000	78	180	•	•	•	•
	24S341	24S343	6	3/4	1200	7000	72	200	•	•	•	•
	24S11	24S13	6	1	1725	7400	80	190	•	•	•	•
	24S31	24S33	6	3	1725	10500	85	220	•	•	—	•
30	30S121	30S123	4	1/2	1725	8000	84	201	•	•	•	•
	30S341	30S343	6	3/4	1200	9000	78	270	•	•	•	•
	30S1121	30S1123	6	1 1/2	1725	11000	90	260	•	•	•	•
	30S21	30S23	6	2	1200	12000	82	285	•	•	—	•
	30S31	30S33	2	3	1725	13000	92	280	•	•	—	•
	36S1121	36S1123	2	1 1/2	1725	14850	86	320	•	•	•	•
36	36S21	36S23	4	2	1725	16000	86	325	•	•	•	•
	36S2A1	36S2A3	6	2	1200	14000	80	325	•	•	—	•
	—	36S33	3	3	1150	19000	82	350	—	•	—	•

### 2 Way Swivel

BLADE DIA.	1-PHASE 115/230V ORDER NO.	3-PHASE 230/460V ORDER NO.	NO. OF BLADES	HP	RPM	0" SP CFM	DB @ 10'	WT.	LIST			
									TE		EXP	
									1 PH.	3 PH.	1 PH.	3 PH.
18	18D141	18D143	4	1/4	1725	3050	72	163	•	•	•	•
	24D141	24D143	2	1/4	1725	5200	78	165	•	•	•	•
24	24D121	24D123	4	1/2	1725	6000	78	180	•	•	•	•
	24D341	24D343	6	3/4	1200	7000	72	200	•	•	•	•
	24D11	24D13	6	1	1725	7400	80	190	•	•	•	•
	24D31	24D33	6	3	1725	10500	85	220	•	•	—	•
30	30D121	30D123	4	1/2	1725	8000	84	201	•	•	•	•
	30D341	30D343	6	3/4	1200	9000	78	270	•	•	•	•
	30D1 121	30D1 123	6	1 1/2	1725	11000	90	260	•	•	•	•
	30D21	30D23	6	2	1200	12000	82	285	•	•	—	•
	30D31	30D33	2	3	1725	13000	92	280	•	•	—	•
	36D1 121	36D1 123	2	1 1/2	1725	14850	86	320	•	•	•	•
36	36D21	36D23	4	2	1725	16000	86	325	•	•	•	•
	36D2A1	36D2A3	6	2	1200	14000	80	325	•	•	—	•
	—	36D33	3	3	1150	19000	82	350	—	•	—	•

NOTE: When ordering explosion proof model add exp. suffix to model number.