


- Available with totally enclosed or explosion proof motor
- Standard props are heavy gauge steel
- Cast aluminum props available for explosion proof requirements
- Heavy 14 gauge steel panel with welded steel pipe bracing
- Cast iron ball bearings in pillow blocks with cast iron sheaves
- Options available: Reverse flow for supply, and acid resistant coating — Call factory

- Guards: Front and rear box available
- Industrial grey enamel finish
- Fans delivered completely assembled, factory tested and adjusted, ready to install
- A special motorized shutter to be used with supply fan, Model WSHM, when shutter is mounted directly in front of fan
- Venturi can also be reversed when flat front surface desired — Request when ordering fan

Dimensions

FAN SIZE	A	B	C
24"	24	30	16
30"	30	36	16
36"	36	42	19
42"	42	48	20
48"	48	54	21
60"	60	66	28



A — Blade Diameter
 B — Panel Size
 C — Depth Dimension
 C Depth dimension varies with motor selection.

Ordering Summary

FAN DIA.	1-PHASE		3-PHASE		PANEL SIZE SQ.	CFM	DB @ 10'	APPROX WT.	LIST			
	115/230V	208-230/460V	HP	RPM					TE		EXP	
	MODEL NO.	MODEL NO.							1 PH.	3 PH.	1 PH.	3 PH.
24"	WEB24G	WEB24G3	1/4	700	30"	5200	60	100	•	•	•	•
	WEB24H	WEB24H3	1/3	775		5760	63	100	•	•	•	•
	WEB24I	WEB24I3	1/2	885		6575	66	130	•	•	•	•
	WEB 24J	WEB24J3	3/4	1015		7545	71	140	•	•	•	•
	WEB24K	WEB24K3	1	1110		7800	73	140	•	•	•	•
30"	WEB30G	WEB30G3	1/4	460	36"	7160	61	140	•	•	•	•
	WEB30H	WEB30H3	1/3	505		7860	63	150	•	•	•	•
	WEB30I	WEB30I3	1/2	580		8500	64	158	•	•	•	•
	WEB30J	WEB30J3	3/4	660		10200	66	168	•	•	•	•
	WEB30K	WEB30K3	1	725		11300	70	168	•	•	•	•
36"	WEB30L	WEB30L3	1 1/2	820	42"	12765	77	178	•	•	•	•
	WEB36H	WEB36H3	1/3	385		9110	64	185	•	•	•	•
	WEB36I	WEB36I3	1/2	440		10405	66	190	•	•	•	•
	WEB36J	WEB36J3	3/4	505		11945	68	200	•	•	•	•
	WEB36K	WEB36K3	1	555		13125	70	200	•	•	•	•
42"	WEB36L	WEB36L3	1 1/2	625	48"	14300	72	210	•	•	•	•
	WEB36M	WEB36M3	2	690		16500	74	230	•	•	•	•
	WEB42H	WEB42H3	1/3	320		11375	64	205	•	•	•	•
	WEB42I	WEB42I3	1/2	365		12980	65	215	•	•	•	•
	WEB42J	WEB42J3	3/4	420		14930	67	225	•	•	•	•
48"	WEB42K	WEB42K3	1	455	54"	16180	69	235	•	•	•	•
	WEB42L	WEB42L3	1 1/2	515		18310	71	240	•	•	•	•
	WEB42M	WEB42M3	2	570		20265	74	245	•	•	•	•
	—	WEB42P3	3	650		23100	79	265	—	•	—	•
	—	WEB48T3	5	620		33100	83	315	—	•	—	•
60"	WEB48I	WEB48I3	1/2	295	66"	15200	69	190	•	•	•	•
	WEB48J	WEB48J3	3/4	335		17300	70	195	•	•	•	•
	WEB48K	WEB48K3	1	370		19100	71	205	•	•	•	•
	WEB48L	WEB48L3	1 1/2	415		21700	72	255	•	•	•	•
	WEB48M	WEB48M3	2	455		24200	74	280	•	•	•	•
60"	—	WEB48P3	3	525	66"	28100	80	305	—	•	—	•
	—	WEB60K3	1	265		24050	76	370	•	•	•	•
	—	WEB60L3	1 1/2	300		27225	77	380	•	•	•	•
	—	WEB60M3	2	390		32200	78	390	•	•	•	•
	—	WEB60P3	3	450		37100	84	405	—	•	—	•
—	WEB60T3	5	540	44600	86	425	—	•	—	•		

NOTE: When ordering Explosion Proof models, add EXP suffix to model number

All units are made to order and are not returnable.