



PLUG IN RADIANT HEATERS




File # E21609

For commercial and industrial applications with Statuary Bronze painted steel enclosure and gold anodized reflector

Ordering Summary

ORDER NUMBER	VOLTS	WATTS	REFLECTIVE ANGLE	DIMENSIONS			SHIP WT. lbs. (Kg)
				HEIGHT in. (mm)	WIDTH in. (mm)	LENGTH in. (mm)	
PRR41512	120	1500	60 Sym	3.375 (86)	5.5 (140)	45 (1168)	9 (4.1)
PRR53024	240	3000				57 (1448)	11 (5.0)



File # E21609



The versatility of these heaters is doubled... They can be mounted on the ceiling or they can be mounted on the optional cart and rolled to any location for maximum spot heating effect. Both heaters have switches for full or 50% operation. For commercial and industrial applications with Statuary Bronze powder coated steel enclosure and gold anodized reflector.

Ordering Summary

ORDER NUMBER	VOLTS	WATTS	REFLECTIVE ANGLE	DIMENSIONS			SHIP WT. lbs. (Kg)
				HEIGHT in. (mm)	WIDTH in. (mm)	LENGTH in. (mm)	
PRR22012	120	2000/1000	60 Sym	3.75 (95)	11 (280)	25 (637)	12 (5.5)
PRR35724	240	5700/2850			19 (484)	34 (866)	22 (10)

Optional Roll Around Cart Accessories

ORDER NUMBER	DESCRIPTION
PRRCART1	Cart to be used with PRR22012
PRRCART2	Cart to be used with PRR35724
Items below do not include cart	
PRRCMK1	Flat Bracket hardware for PMRR22012
PRRCMK2	Flat Bracket hardware for PMRR35724

